



Data sheet Vibrating grizzly

Project name
 Project no.
 Tag no.
 Tag description

Document no.
 Revision no.
 P&ID no.
 Status

	Originator	Date	Checked by	Date
Process				
Mechanical				
Electrical				
Approved by		Date	Professional registration no.	
Client (if applicable)				
Lead engineer				

General information

Corrosion protection	Reference drawing no.
Engineering specifications	Service
Installation	
Remarks	

Site

Altitude(AMSL)	m	Location	
Ambient temperature maximum	°C	Rainfall	mm/y
Ambient temperature minimum	°C	Wind velocity	km/h
Barometric pressure	kPa	Humidity	%
Underground atmospheric classification		Class	Division

Process

Feed material data			
General description of application			
Material handled		Angle of repose	degree
Capacity minimum	t/h	Angle of surcharge	degree
Capacity normal	t/h	Moisture content (free)	%
Capacity maximum	t/h	Operating days per annum	days
Temperature normal	°C	Operating hours per day	hours
Particle shape		Feed from static head	
Particle size maximum	mm	Drop height	mm
Top deck cut size	mm	Feed type	continuous/intermittent
Bottom deck cut size	mm	Screening	wet/dry
No. of screen decks		Availability	%
Material characteristics			
Abrasive	yes/no	Erosive	yes/no
Combustible	yes/no	Flowability	free/poor/sticky
Corrosive	yes/no	Friable	yes/no
Dusty	yes/no	Hygroscopic	yes/no
Explosive	yes/no	Toxic	yes/no



Data sheet Vibrating grizzly

Project name
 Project no.
 Tag no.
 Tag description

Document no.
 Revision no.
 P&ID no.
 Status

Feed stream particle size distribution data				
Component	Size	Cumulative % passing		
Size 1	mm			%
Size 2	mm			%
Size 3	mm			%
Size 4	mm			%
Size 5	mm			%
Size 6	mm			%
Size 7	mm			%
Size 8	mm			%
Size 9	mm			%
Size 10	mm			%
Size 11	mm			%
Size 12	mm			%
Distribution d ₅₀	mm	Maximum agglomerated size		mm
Maximum size	mm			
Product material data				
	Oversize	Undersize	Intermediate	
Size minimum	mm	mm		mm
Size maximum	mm	mm		mm
Discharge rate normal	t/h	t/h		t/h
Discharge rate maximum	t/h	t/h		t/h
Discharge rate minimum	t/h	t/h		t/h
Screening efficiency	%	%		%
Product stream particle size distribution data				
Component	Size	Cumulative % passing		
Size 1	mm			%
Size 2	mm			%
Size 3	mm			%
Size 4	mm			%
Size 5	mm			%
Size 6	mm			%
Size 7	mm			%
Size 8	mm			%
Size 9	mm			%
Size 10	mm			%
Size 11	mm			%
Size 12	mm			%
Distribution d ₅₀	mm	Maximum agglomerated size		mm
Maximum size	mm			



Data sheet Vibrating grizzly

Project name
 Project no.
 Tag no.
 Tag description

Document no.
 Revision no.
 P&ID no.
 Status

Mechanical

Design data								
Design capacity	t/h	Screen overall length						mm
Capacity minimum	t/h	Screen overall width						mm
Maximum head above feed	m	Screen overall height						mm
Inclination maximum	degree	Trough length						mm
Inclination minimum	degree	Trough width						mm
Type of deck motion		Trough height						mm
Supports front	yes/no	Supports rear						yes/no
Sound intensity actual @ 1m	db							
Support loadings								
		Static		Dynamic normal		Dynamic maximum		
		Front	Rear	Front	Rear	Front	Rear	
Vertical								
Horizontal							kN	
Information to be supplied by vendor								
Screen requirements								
		Top		Intermediate		Lower		
Total area								m ²
Bland feed length								m
Screening length								m
Bland discharge length								m
Total screen area								m ²
Free screen area								m ²
Aperture size								mm
Perforation shape								
Deck section area								m ²
Deck section width								m
Deck section fasten								
Inclination of deck								degree
Number of spray bars required								
Spray water flow								m ³ /h
Spray water pressure								kPa(g)
Materials of construction								
		Material				Thickness		
Screening surface						mm		
Trough base						mm		
Trough frame						mm		
Trough liner						mm		
Trough sides						mm		



Data sheet Vibrating grizzly

Project name
 Project no.
 Tag no.
 Tag description

Document no.
 Revision no.
 P&ID no.
 Status

Drive information			
Manufacturer		Full load torque at start	N
Type		Full load torque running	N
Vibrating frequency	Hz	Amplitude	mm
Electrical			
System information			
Supply voltage	V	Type of system earthing	
Voltage variations	V	Area classification (SABS 0108)	
Maximum voltage unbalance	%	Hazardous gas/dust	
Total voltage harmonic content	%	Cable size	mm ²
Supply frequency	Hz	Cable type	
Temperature classification of gas/dust			
Data to be supplied by vendor			
Manufacturer		Equivalent circuit	
Frame size		Winding connection	
Year of manufacture		Insulation class	
Serial number		Insulation type	
Rating	kW	Method of cooling (IC Code)	
Full load current	A	Method of mounting (IM Code)	
Class of rating (IEC 60034-1 class 4 2)		Lubricant type/grade	
Enclosure classification IP code		Type of explosion protection	
Power factor at 100% load		Efficiency at 100% load	%
Power factor at 75% load		Efficiency at 75% load	%
Power factor at 50% load		Efficiency at 50% load	%
Temperature rise	°C	Break away torque	Nm
Locked rotor current	A	Pull out torque	Nm
Locked rotor power factor		Pull up torque	Nm
Locked rotor withstand time cold	s	Full load torque	Nm
Locked rotor withstand time warm	s	Moment of inertia of load (MIL)	kg/m ²
Allowable no. of starts per hour cold		Moment of inertia of motor rotor	kg/m ²
Allowable no. of starts per hour warm		MIL referred to motor shaft	kg/m ²
Maximum thrust continuous (down)		Temperature rating	
Maximum thrust momentary (down)		Sound intensity	db
Type of bearing non-drive end		Type of bearing drive end	
Direction of rotation viewed from non-drive end			
Terminal box position viewed from non-drive end			
Speed vs. torque curve at full volts required			
Speed vs. torque curve at 85% full volts required			
Speed vs. current curve at full volts required			
Speed vs. current curve at 85% full volts required			
Speed vs. power curve at full volts required			
Speed vs. power curve at 85% full volts required			



Data sheet Vibrating grizzly

Project name
 Project no.
 Tag no.
 Tag description

Document no.
 Revision no.
 P&ID no.
 Status

Inspection & testing			
Mechanical		Electrical	
Motion amplitude		Shop inspection required	
Shipping & installation			
Information to be supplied by vendor			
Heaviest lift	kg	Overall height	mm
Heaviest maintenance lift	kg	Overall length	mm
Weight driver	kg	Overall width	mm
Maximum foundation loading	kg	Total shipping weight	kg
Net weight	kg	Total shipping volume	m ³
Operating weight	kg		
Underground dimensions			
Underground applicable		Cage length	mm
Headroom available	mm	Cage width	mm